

Graffiti Guard

Water-Based Graffiti Preventative

Product Description

Ameripolish® Graffiti Guard is a water-based penetrating protective sealer, designed to defend masonry, metal, and cementitious material from paint, soot, dirt, and other material that can be found obscuring walls and surfaces around the world. By forming a protective barrier, Graffiti Guard allows for easy removal of unwanted “graffiti” from cementitious surfaces and back to its original and intended aesthetic appearance. Graffiti Guard leaves behind no shine, or aesthetically altering appearance.

Features

- RTU = Ready to use
- Non-Hazardous
- Creates barrier to prevent unwanted contaminants from adhering to the surface.
- Easily remove graffiti after it has been applied to the surface with the minimum of a cold/warm water power washer (1500 PSI minimum)
- Protects from soot, and smog in urban environments
- Low-odor, non-flammable, VOC compliant (<5g/L)

Uses

Ameripolish® Graffiti Guard is ideal to be used on:

- New or existing cementitious and masonry surfaces

Dilution & Coverage

Ameripolish® Graffiti Guard is shipped Ready to Use (RTU). Ameripolish® Graffiti Guard will cover 400-2000 square feet per gallon depending on porosity of the surface.

Application

On Masonry and Cementitious Surfaces

1. Prior to starting project, apply Graffiti Guard to sample area of each surface type to be treated, using application procedures proposed for project. Confirm that surface is receptive to sealer.
2. Ambient temperature during application should be 55°F-80°F (12.8°C-26.7°C). Do not apply on rainy, foggy, or extremely humid days. Excess moisture may

Product Specification

Application:	Spray
Appearance:	Milky liquid
VOC:	Compliant (5g/l)
Shelf life:	1 year
Solvent:	Water-based

Packaging Specification

Product #	Shipping Wt.	Container
GG-1	10 lbs.	1 gallon RTU
GG-5	50 lbs.	5 gallons RTU
GG-30	300 lbs.	30 gallons RTU
GG-55	550 lbs.	55 gallons RTU
GG-250	2,500 lbs.	250 gallons RTU



Graffiti Guard

Water-Based Graffiti Preventative

- prevent sealer from drying properly.
3. Apply Graffiti Guard using an acetone safe pump sprayer, airless sprayer, battery operated sprayer or other safety certified sprayers with a conical tip.
 4. Spray Graffiti Guard with sprayer in circular motions approximately 12 inches from the project surface to ensure full coverage.
 5. Apply 2 applications of Ameripolish® Graffiti Guard to the surface to ensure full coverage.
 6. Allow time for surface to dry

On Metal Surfaces

Product should be rolled with a paint roller to provide consistent coverage and avoid “drip marks”. Allow time for the surface to dry.

Cleanup

Clean tools and equipment immediately with water. Always remove rundown and spills immediately.

Preparation

WARNING: People, property, vehicles, animals, plants, and all surfaces not intended to be sealed should be protected from the product, splash, over-spray, and wind drift, using polyethylene sheeting or other proven protective material. High moisture levels may affect performance of sealer. Do not apply if surfaces are frozen, dirty or has standing water. Remove oil, dirt, was, paints, and other sealers; pressure wash and/or power scrub if necessary. Ameripolish® Strip & Clean™ is highly recommended to clean the surface.

Storage

- Store upright in safe dry place at 40-110F° (4 -43C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

VOC Compliance

In addition, Ameripolish® Graffiti Guard offers VOC compliance with low VOC at 5g/L and is also compliant with national, state and district regulations:

- US Environmental Protection Agency
- California Air Resources Board SCM Districts*
- South Coast Air Quality Management District*
- Maricopa County, AZ
- Northeast Ozone Transport Commission*

*Before application, verify product conformance with local and state codes.

Warning & Safety Information

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be found online at www.ameripolish.com or upon request by contacting Ameripolish at 1-800-592-9320.

Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.